

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
21 December 2000 (21.12.2000)

PCT

(10) International Publication Number
WO 00/76573 A1

(51) International Patent Classification⁷: **A61M 31/00**,
A61L 27/54, 29/16, 31/16

(21) International Application Number: PCT/US00/15102

(22) International Filing Date: 2 June 2000 (02.06.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/333,032 15 June 1999 (15.06.1999) US

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant: SCIMED LIFE SYSTEMS, INC. [US/US];
One Scimed Place, Maple Grove, MN 55311-1566 (US).

Published:

— With international search report.


--- Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.

(72) Inventor: PALASIS, Maria; 65 Martin Road, Wellesley, MA 02181 (US).

(74) Agents: BRAINARD, Charles, R. et al.; Kenyon & Kenyon, Suite 700, 1500 K Street, N.W., Washington, DC 20005 (US).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: LOCALIZED RELEASE OF GENETIC INFORMATION FROM BIOSTABLE COATING MATERIALS



(57) Abstract: Medical devices and systems for the localized delivery of genetic information to a target location within a mammalian body. In one embodiment, the system comprises a medical device insertable into the body and a biostable coating over at least part of the medical device. Genetic information is incorporated into the biostable coating before the medical device is placed into the body, and is released from the biostable coating at a target location within the body. The invention also includes methods for the localized delivery of genetic information to target locations within a mammalian body using the medical devices and systems of the invention.

WO 00/76573 A1

LOCALIZED RELEASE OF GENETIC INFORMATION FROM BIOSTABLE COATING MATERIALS

5 Field of the Invention

The present invention relates to the localized delivery of genetic information to target locations within the mammalian body, and more particularly to the delivery of genetic information from biostable materials coated onto medical devices.

10

Background of the Invention

The treatment of disease such as vascular disease by local pharmacotherapy presents a means of delivering therapeutic drug doses to target tissues while minimizing systemic side effects. Recently, for example,
15 the local delivery of gene constructs to effect vascular response has gained increased interest. Gene transfection of vascular smooth muscle cells in vivo, however, is often difficult because of the low transfer efficiency attributed in

part to inefficient local delivery devices and to the barrier properties of the vessel wall.

As an example of localized delivery of therapeutic agents, in vivo adenoviral gene transfer has been accomplished with the use of site-specific delivery catheters. Because genetic materials are typically in the form of large molecules, however, it has been difficult to engineer biostable delivery materials that can hold the genetic materials during delivery within the body and then release the genetic materials upon reaching a target location. Rather, such delivery is accomplished by incorporating the genetic information into a biodegradable medical device or coating, whereby the genetic information is released as the biodegradable material disintegrates while in the body. The use of biodegradable materials within the body, however, often results in adverse interactions with tissue and the resultant inflammation thereof. Further, biodegradable materials are generally characterized by a short shelf-life because they typically degrade upon exposure to the ambient atmosphere.

Summary of the Invention

In one aspect, the present invention relates to a system for the localized delivery of genetic information to a target location within a mammalian body. In one embodiment, the system comprises a medical device insertable into the body and a biostable coating over at least part of the medical device. Genetic information is incorporated into the biostable

coating before the medical device is placed into the body, and is released from the biostable coating at a target location within the body.

In another aspect, the present invention relates to method for the localized delivery of genetic information to a target location within a mammalian body. In one embodiment, the method includes the steps of providing a medical device insertable into the body, coating at least a portion of the medical device with a biostable material, incorporating the genetic information into the biostable material, and placing the medical device at the target location. The genetic information is released from the biostable material at the target location.

In another aspect, the present invention relates to medical devices at least partially covered with a biostable coating that facilitates the localized delivery of genetic information.

One advantage of the present invention is that it provides biostable coatings for medical devices, and methods of making such coatings, that are suitable for holding and releasing genetic information.

Another advantage of the present invention is that it provides for the localized delivery of genetic information from biostable materials, thus avoiding the potential problems of delivery from biodegradable polymers.

Yet another advantage of the present invention is that it provides for the localized delivery of genetic information in a controlled and reproducible manner.

Brief Description of the Drawings

Fig. 1 shows a medical device coated with a porous coating for the localized delivery of genetic information, in accordance with an embodiment of the invention.

5 Fig. 2 shows a normal view of a polymer structure having an interconnected pore structure, in accordance with an embodiment of the invention.

Fig. 3 shows a cross-sectional fracture surface of a polymer structure having an interconnected pore structure, in accordance with an
10 embodiment of the present invention.

Fig. 4 shows a graph of albumin released from porous polymer coatings in release experiments, in accordance with an embodiment of the present invention.

15 Detailed Description

The present invention provides for the localized delivery of genetic information to target locations within the body. The delivery systems, methods and medical devices of the invention are novel in that they make use of biostable coating materials to deliver the genetic information to the target
20 locations. As used herein, "biostable materials" refer to those materials that do not undergo significant degradation upon prolonged exposure (*i.e.*, up to six months, a year, or longer) to bodily fluids, tissues, and the like. The biostable coating materials of certain embodiments of the invention are

porous polymer materials that are characterized by interconnected pores of sufficient size to allow for the incorporation therein, and release therefrom, of genetic information.

The biostable, porous polymer materials of the present invention
5 are formed by methods not previously used to form coatings on medical devices and are thus characterized by novel coating properties. The porous polymer materials are preferably characterized by an average pore diameter of at least about 5 microns, more preferably at least about 8 microns, and more preferably at least about 10 microns.

10 In one embodiment, polymer coatings containing large interconnected pores are formed by a freeze-dried process in which a medical device is coated with an aqueous polymer solution that is rapidly frozen and then lyophilized. During lyophilization, ice within the coating sublimates from the coating to leave an interconnected pore structure. The size of the
15 resulting pores is controlled by processing parameters such as the freezing rate during the freeze-drying process, and the water content of the pre-coating formulation. The result of the freeze-drying process is a medical device coated with a biostable polymer coating characterized by an interconnected pore structure that is capable of having genetic information
20 incorporated therein.

Suitable polymers for use in embodiments wherein a porous structure is obtained by freeze-drying include any suitable biostable polymer, such as polyurethanes (including polyurethane dispersions), ethylene

vinylacetate polymers, hydrogels such as crosslinked gelatin, dextran, polycarboxylic acids, cellulosic polymers, gelatin, polyvinylpyrrolidone, maleic anhydride polymers, acrylic latex dispersions, polyamides, polyvinyl alcohols, polyethylene oxides, glycosaminoglycans, polysaccharides, polyesters, 5 polyacrylamides, polyethers, and blends and copolymers thereof.

In accordance with the invention, the genetic information delivered by polymer coatings that are freeze-dried is incorporated into the polymer either during or after coating formation. In the former case, the genetic information is, for example, placed into solution with an aqueous 10 dispersion of polymer (or alternatively, an emulsion or dispersion of a water-based solution of genetic information is placed into solution with a polymer in an organic solvent such as methylene chloride), which is thereafter applied to the medical device as a coating. In the latter case, the genetic information is applied to the coating by absorption, such as by dipping. In this situation, 15 the coating preferably consists of a blend of a charged polymer and a neutral flexible polymer, wherein the charged polymer interacts with oppositely charged genetic information and the flexible polymer provides desired mechanical properties required for a device coating. The charged polymer allows for the rapid loading of large quantities of genetic information, and 20 results in a delivery rate that is dependent on the size of the pores as well as the rate of dissociation between the genetic information and the charged polymer.

In certain other embodiments, polymer coatings containing large interconnected pores are formed by incorporating water-soluble particles into a polymer coating during fabrication thereof. For example, water-soluble particles are dispersed in a solution of dissolved polymer such that a stable dispersion is formed. This solution is coated onto a medical device and dried. The coating is thereafter exposed to water, thus allowing the water-soluble particles to dissolve and diffuse out of the coating. The result is a polymer coating characterized by a large, interconnected pore structure, the size of which depends on factors such as the molecular weight of the water-soluble particles and/or the weight ratio of the water-soluble particles to the polymer. Genetic information is then loaded into the coating by any suitable means, such as by dipping or spraying. As an alternative to loading the genetic information after the diffusion of water-soluble particles out of the coating, the genetic information is incorporated into the coating during fabrication thereof. In this latter case, both the genetic information and the water-soluble particles exist in the coating until released upon delivery into the body, and the water-soluble particles are either inert or bioactive additives.

The medical devices onto which the biostable coatings of the invention are placed include any suitable device including implantable devices such as catheters, stents, needle injection devices, blood clot filters, vascular grafts, stent grafts, biliary stents, colonic stents, bronchial/pulmonary stents, esophageal stents, ureteral stents, aneurysm filling coils and other coiled coil devices, trans myocardial revascularization ("TMR") devices, percutaneous

myocardial revascularization ("PMR") devices etc., as are known in the art, as well as devices such as hypodermic needles, soft tissue clips, holding devices, muscle implants and other types of medically useful devices. Such devices are delivered to and/or implanted at target locations by known techniques. Delivery is optionally performed with a sheath that covers the coated medical device to help inhibit the release of the genetic information prior to reaching a target location.

Fig. 1 shows a coated vascular stent 100 as an example of a coated medical device of the present invention. The coated stent 100 includes a stent structure 110 having struts 120 of any suitable metallic or polymeric material, as is known in the art. At least part of the stent structure 110 includes a biostable coating 130 capable of incorporating and releasing genetic information.

Useful therapeutic applications to which the present invention can be applied include, without limitation, methods for treating, ameliorating, reducing and/or inhibiting any lumen or tissue injury, including those that result in denuding the interior wall of a lumen, namely its endothelial lining, including the lining of a blood vessel, urethra, ureter, lung, colon, urethra, biliary tree, esophagus, prostate, fallopian tubes, uterus, vascular graft, or the like. Such injuries result from disease, as in the case of atherosclerosis or urethral hyperplasia (strictures), and/or from mechanical injury from, for example, deployment of an endolumenal stent or a catheter-based device, including balloon angioplasty and related devices.

Vascular therapies that benefit using the methods disclosed herein include, without limitation, cardiomyopathies, cardiac and cerebral strokes, embolisms, aneurysms, atherosclerosis, and peripheral and cardiac ischemias. Delivery of genes encoding proteins competent to induce collateral blood vessel formation can be used to advantage in treating these disorders. Delivery of genes encoding proteins competent to interfere with neointimal (smooth muscle) cell proliferation also is particularly useful in treating restenosis.

Non-vascular therapies that benefit using the methods disclosed herein include biliary, uretal strictures, and urogenital applications including therapies for incontinence, kidney stones and the like. Here devices typically are implanted for a prescribed period of time and local delivery of genetic agents competent to induce an antibacterial, anti-inflammatory, or anti-encrustation effect are advantageous. In other applications, the delivery of genetic anti-inflammatory agents is used to treat prostatitis, interstitial cystitis and other urogenital inflammatory disorders. Genetic antiproliferative agents can also be used in endometriosis therapies. Still another application is in the delivery of genetic anticancer agents. The methods of the invention can be applied to therapies for bladder, prostate and uterine cancer.

Specific examples of genetic information used in conjunction with the present invention include, for example, nucleic acids (including, for example, recombinant nucleic acids; naked DNA, cDNA, RNA; genomic DNA, cDNA or RNA in a non-infectious vector or in a viral vector which may have

attached peptide targeting sequences; antisense nucleic acid (RNA or DNA);
and DNA chimeras which include gene sequences and encoding for ferry
proteins such as membrane translocating sequences ("MTS") and herpes
simplex virus-1 ("VP22")); oligonucleotides; ribozymes; anti-sense genes;
5 DNA compacting agents; and gene/vector systems (*i.e.*, anything that allows
for the uptake and expression of nucleic acids).

Examples of therapeutic polynucleotides include anti-sense
DNA and RNA; DNA coding for an anti-sense RNA; or DNA coding for tRNA
or rRNA to replace defective or deficient endogenous molecules. The
10 polynucleotides of the invention can also code for therapeutic proteins or
polypeptides. Included are survival genes which protect against cell death,
such as anti-apoptotic Bcl-2 family factors and Akt kinase; anti-proliferative
genes such as Fas Ligand, thymidine kinase / ganciclovir, and cell cycle
inhibitors such as CDK inhibitors, Rb and E2F. Still other useful factors
15 include those inhibiting restenosis, angiogenic factors such as bFGF, aFGF,
VEGF, HIF1, Del1, PIGF, PDGF, VEGF, vascular endothelial growth factor,
epidermal growth factor, transforming growth factor α and β , platelet-derived
endothelial growth factor, platelet-derived growth factor, tumor necrosis factor
 α , hepatocyte growth factor, and insulin like growth factor DNA encoding
20 polypeptides including monocyte chemoattractant protein ("MCP-1"), and the
family of bone morphogenic proteins ("BMP's"). The known proteins include
BMP-2, BMP-3, BMP-4, BMP-5, BMP-6 (Vgr-1), BMP-7 (OP-1), BMP-8, BMP-
9, BMP-10, BMP-11, BMP-12, BMP-13, BMP-14, BMP-15, and BMP-16.

Currently preferred BMP's are any of BMP-2, BMP-3, BMP-4, BMP-5, BMP-6 and BMP-7. These dimeric proteins can be provided as homodimers, heterodimers, or combinations thereof, alone or together with other molecules. Alternatively or, in addition, molecules capable of inducing an upstream or downstream effect of a BMP can be provided. Such molecules include any of the "hedgehog" proteins, or the DNA's encoding them.

The present invention is further described with reference to the following non-limiting examples.

10 Example 1 - Formation of Interconnected Pore Structure

Polymer coatings characterized by interconnected pore structures were made by a freeze-dry process, in accordance with the present invention.

An aqueous solution of albumin and bahydrol, an aqueous dispersion of polyurethane, was prepared by mixing 10 wt% albumin and 20 wt% bahydrol in solution. Albumin was used as a substitute for genetic molecules. Stainless steel coupons measuring approximately 1 cm x 2 cm were dipped into the solution for about 30 seconds to form coatings over the coupons, and then immediately subjected to low temperature environments (i.e., -20° and -80°C) to freeze the at least partially-liquid coatings. The coupons were then placed in a lyophilizer to sublime the frozen water in the coatings.

The freeze-dry process resulted in polyurethane coatings characterized by a substantially uniform, interconnected pore structures. The final coating composition was about 33% albumin - 67% bayhydrol. Fig. 2 is a representative scanning electron micrograph showing the top surface of coatings formed by the process employing the -80°C freezing temperature. Fig. 3 shows a fracture surface of the coating shown in Fig. 2, thus illustrating the interconnected nature of the pore structure. Generally, the lower freezing temperature (*i.e.*, -80°C) resulted in smaller pores, and higher pore densities, than the higher freezing temperature (*i.e.*, -20°C).

Example 2 - Effect of Drying Time on Pore Structure

Porous polyurethane coatings were formed on coupons in accordance with Example 1. To observe the effects on drying time between dipping the coupons into the polymer solution and placing the coupons into a -80°C environment, coated coupons were dried in air for time periods of 0, 30, 60 and 300 seconds prior to lyophilization.

The pore sizes resulting from the freeze-dry process were inversely related to drying time. The variation in approximate pore dimensions as a function of drying time are displayed in Table I.

Table I: Pore Dimensions as a Function of Drying Time Prior to Freezing.

Drying Time (s)	Approximate Avg. Pore Diameter (microns)
0	9
30	8.5
60	2
300	0

Example 3 - Release of Albumin from Porous Coatings

The coated coupons formed in accordance with Example 1 were placed in phosphate buffered saline for up to 60 minutes to observe the release profiles of albumin from the porous coatings. As a control group, coupons were coated with the polyurethane-albumin solution and allowed to dry in air without freezing. The polymer coatings on the control coupons were thus not characterized by an interconnected porous structure.

Fig. 4 shows typical release profiles of tested samples. As can be seen by Fig. 4, there was no statistically significant difference between the release profiles for samples formed in accordance with Example 1 (i.e., samples freeze-dried using -20°C and -80°C freezing temperatures). There was, however, a distinct difference between the release from the freeze-dried coupons and those coupons not freeze-dried. Whereas only about 40% of the loaded albumin was released from the coupons not freeze-dried after 60

minutes, about 90% of the loaded albumin was released from the freeze-dried coupons during the same time period. Moreover, whereas the release of albumin from the coupons not freeze-dried was substantially complete after about 10 minutes, the release from the freeze-dried coupons continued
5 throughout the 60-minute test period.

This Example demonstrates that the porous polymer coatings made in accordance with the present invention are well-suited to the efficient release of large molecule materials such as genetic molecules.

10 The present invention provides for the localized delivery of genetic information to target locations within the body by medical devices coated with biostable coating delivery materials. To facilitate this purpose, the biostable coating materials of certain embodiments of the invention are porous polymer materials that are characterized by interconnected pores of
15 sufficient size to allow for the incorporation therein, and release therefrom, of genetic information. Although the present invention has been described with respect to several exemplary embodiments, there are many other variations of the above-described embodiments which will be apparent to those skilled in the art, even where elements have not explicitly been designated as
20 exemplary. It is understood that these modifications are within the teaching of the present invention, which is to be limited only by the claims appended hereto.

I Claim:

- 1 1. A system for the localized delivery of genetic information to a target
2 location within a mammalian body, comprising:
3 a medical device insertable into the body; and
4 a biostable coating over at least part of said device;
5 wherein the genetic information is incorporated into said biostable
6 coating prior to insertion of said medical device into the body and
7 released from said biostable coating at said target location.

- 1 2. The system of claim 1, wherein said biostable coating comprises a
2 material selected from the group consisting of polyurethanes, ethylene
3 vinylacetate polymers, hydrogels, crosslinked gelatin, dextran,
4 cellulose, and blends and copolymers thereof.

- 1 3. The system of claim 1, wherein said biostable coating is made by a
2 freeze-drying process.

- 1 4. The system of claim 1, wherein said biostable coating is made by a
2 process comprising the steps of:
3 placing water-soluble particles into a solution comprising a
4 biostable polymer;
5 coating said medical device with said solution to form a coating;

6 drying said coating; and
7 exposing said coating to an aqueous environment.

1 5. The system of claim 1, wherein said biostable coating is characterized
2 by an interconnected pore structure.

1 6. The system of claim 5, wherein said interconnected pore structure has
2 an average pore diameter of at least about 5 microns.

1 7. The system of claim 5, wherein said interconnected pore structure has
2 an average pore diameter of at least about 10 microns.

1 8. The system of claim 1, wherein said genetic information comprises a
2 material selected from the group consisting of nucleic acids,
3 oligonucleotides, DNA compacting agents, recombinant nucleic acids,
4 and gene/vector systems.

1 9. The system of claim 1, wherein said medical device comprises a stent.

1 10. The system of claim 1, wherein said medical device comprises a
2 catheter.

1 11. The system of claim 1, wherein said medical device comprises a
2 needle.

1 12. The system of claim 1, wherein said medical device comprises a blood
2 filter.

1 13. The system of claim 1, wherein said medical device comprises a tissue
2 clip.

1 14. A method for the localized delivery of genetic information to a target
2 location within a mammalian body, comprising the steps of:
3 providing a medical device insertable into the body;
4 coating at least a portion of said device with a biostable
5 material;
6 incorporating the genetic information into said biostable
7 material; and
8 placing said medical device at the target location;
9 wherein the genetic information is released from said biostable
10 material at the target location.

1 15. The method of claim 14, wherein said step of coating at least a portion
2 of said device with a biostable material comprises the steps of:
3 forming an aqueous solution of said biostable material;

4 placing said at least a portion of said device into contact with
5 said solution to form a coating of said biostable material on said
6 device;
7 subjecting said coating to a temperature of 0° Celsius or less
8 before said coating is completely dry;
9 lyophilizing said coating.

1 16. The method of claim 15, wherein said step of incorporating the genetic
2 information into said biostable material comprises the step of placing
3 said genetic information into said aqueous solution of biostable
4 material.

1 17. The method of claim 15, wherein said step of incorporating the genetic
2 information into said biostable material comprises the step of placing
3 said coating into contact with said coating after said step of lyophilizing
4 said coating.

1 18. The method of claim 15, wherein said step of subjecting said coating
2 to a temperature of 0° Celsius or less takes place within about 60
3 seconds from said step of placing said at least a portion of said device
4 into contact with said solution.

- 1 19. The method of claim 15, wherein said step of subjecting said coating
2 to a temperature of 0° Celsius or less takes place within about 30
3 seconds from said step of placing said at least a portion of said device
4 into contact with said solution.
- 1 20. The method of claim 15, wherein said temperature is about -20°
2 Celsius or less.
- 1 21. The method of claim 15, wherein said step of lyophilizing said coating
2 results in the formation of an interconnected pore structure within said
3 coating.
- 1 22. The method of claim 14, wherein said step of coating at least a portion
2 of said device with a biostable material comprises the steps of:
3 placing water-soluble particles into a solution comprising said
4 biostable material;
5 coating said medical device with said solution to form a coating;
6 drying said coating; and
7 exposing said coating to an aqueous environment.
- 1 23. The method of claim 14, wherein said biostable material comprises a
2 material selected from the group consisting of polyurethane, ethylene
3 vinylacetate, hydrogels, and blends and copolymers thereof.

1 24. The method of claim 14, wherein said genetic information comprises
2 a material selected from the group consisting of nucleic acids,
3 oligonucleotides, DNA compacting agents, recombinant nucleic acids,
4 and gene/vector systems.

1 25. A medical device having a freeze-dried coating on at least a portion
2 thereof.

1 26. The medical device of claim 25, wherein said coating comprises a
2 biostable material.

1 27. The medical device of claim 26, wherein said biostable material
2 comprises a material selected from the group consisting of
3 polyurethane, ethylene vinylacetate, hydrogels, and blends and
4 copolymers thereof.

1 28. The medical device of claim 25, further comprising genetic information
2 incorporated into said coating.

1 29. The medical device of claim 28, wherein said genetic information
2 comprises a material selected from the group consisting of nucleic

3 acids, oligonucleotides, DNA compacting agents, recombinant nucleic
4 acids, and gene/vector systems.


1 30. The medical device of claim 25, wherein said medical device
2 comprises a stent.

1 31. The medical device of claim 25, wherein said medical device
2 comprises a catheter.


1 32. The medical device of claim 25, wherein said medical device
2 comprises a needle.

1 33. The medical device of claim 25, wherein said medical device
2 comprises a blood filter.

1 34. The medical device of claim 25, wherein said medical device
2 comprises a tissue clip.



AA
Fig. 1






Fig. 2




Fig. 3




Fig. 4

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 00/15102

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61M31/00 A61L27/54 A61L29/16 A61L31/16

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61M A61L A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No
X	US 5 674 192 A (BARRY ET AL.) 7 October 1997 (1997-10-07)	1,2,5-13
Y	abstract column 1, line 50 - line 67 column 2, line 12 - line 15 column 2, line 33 - line 35 column 3, line 39 - line 43 column 7, line 14 - line 22 column 12, line 10 - line 38; claims 1,2,10,11; figures 2-6 ---	3,4, 26-34
Y	US 5 660 854 A (BODEKER ET AL.) 26 August 1997 (1997-08-26) abstract column 4, line 15 - line 52 column 8, line 28 - line 49; claims 1,2,4 ---	3,4
	-/--	



Further documents are listed in the continuation of box C



Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"S" document member of the same patent family

Date of the actual completion of the international search

6 October 2000

Date of mailing of the international search report

13/10/2000

Name and mailing address of the ISA

European Patent Office, P B 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Michels, N

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 00/15102

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 344 654 A (KUBERASAMPATH ET AL.) 6 September 1994 (1994-09-06)	25
Y	abstract column 3, line 45 - line 66 column 10, line 29 - line 34; figure 1	26-34
A	US 5 156 844 A (AEBISCHER ET AL.) 20 October 1992 (1992-10-20) abstract column 3, line 14 - column 4, line 33; claims 1,5,6,11,12; figures 1A-C; example 3	1-13, 25-34
A	US 5 865 796 A (MCCABE) 2 February 1999 (1999-02-02) abstract column 2, line 17 - line 29 column 3, line 6 - line 38; example 1	1-13, 25-34
A	EP 0 835 894 A (INST TEXTIL & FASERFORSCHUNG) 15 April 1998 (1998-04-15) abstract page 6, line 12 - line 14; example 13	25

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-13

A medical device with a coating releasing a carrier for a genetic information

2. Claims: 25-34

A medical device with a freeze-dried coating

INTERNATIONAL SEARCH REPORT

Information on patent family members

I. International Application No

PCT/US 00/15102

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5674192 A	07-10-1997	US 5304121 A	19-04-1994
		CA 2166101 A	02-02-1995
		EP 0708671 A	01-05-1996
		JP 9500561 T	21-01-1997
		WO 9503083 A	02-02-1995
		US 5954706 A	21-09-1999
		US 5843089 A	01-12-1998
		CA 2098984 A	29-06-1992
		DE 69131486 D	02-09-1999
		DE 69131486 T	17-02-2000
		EP 0565604 A	20-10-1993
		EP 0920843 A	09-06-1999
		ES 2137179 T	16-12-1999
		JP 6503984 T	12-05-1994
		WO 9211896 A	23-07-1992
		WO 9211895 A	23-07-1992
US 5660854 A	26-08-1997	AU 698113 B	22-10-1998
		AU 4364096 A	19-06-1996
		CA 2206259 A	06-06-1996
		EP 0790823 A	27-08-1997
		JP 10511019 T	27-10-1998
		WO 9616643 A	06-06-1996
		US 5972366 A	26-10-1999
US 5344654 A	06-09-1994	US 4968590 A	06-11-1990
		US 5011691 A	30-04-1991
		US 4975526 A	04-12-1990
		US 5171574 A	15-12-1992
		US 5108753 A	28-04-1992
		US 5182365 A	26-01-1993
		US 5250302 A	05-10-1993
		US 5266683 A	30-11-1993
		US 5162114 A	10-11-1992
		AU 668411 B	02-05-1996
		AU 4599793 A	04-01-1994
		CA 2138270 A	23-12-1993
		EP 0646022 A	05-04-1995
		JP 2908563 B	21-06-1999
		JP 7504680 T	25-05-1995
		WO 9325246 A	23-12-1993
		AT 142644 T	15-09-1996
		AT 134647 T	15-03-1996
		AU 628050 B	10-09-1992
		AU 3444989 A	03-11-1989
		AU 618357 B	19-12-1991
		AU 3530589 A	03-11-1989
		CA 1338663 A	22-10-1996
		DE 68925773 D	04-04-1996
		DE 68925773 T	17-10-1996
		DE 68927153 D	17-10-1996
		DE 68927153 T	06-03-1997
		EP 0372031 A	13-06-1990
		EP 0362367 A	11-04-1990
		EP 0714665 A	05-06-1996
		EP 0723013 A	24-07-1996
		JP 2933867 B	16-08-1999
		JP 8336390 A	24-12-1996

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No
PCT/US 00/15102

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5344654 A		JP 2869381 B	10-03-1999
		JP 8322570 A	10-12-1996
		JP 8187084 A	23-07-1996
		JP 2522568 B	07-08-1996
		JP 3500655 T	14-02-1991
		JP 2548414 B	30-10-1996
		JP 3502579 T	13-06-1991
		WO 8909787 A	19-10-1989
		WO 8909788 A	19-10-1989
		US 5750651 A	12-05-1998
		US 5468845 A	21-11-1995
		US 5496552 A	05-03-1996
		US 5670336 A	23-09-1997
		US 5814604 A	29-09-1998
		US 5714589 A	03-02-1998
		US 5958441 A	28-09-1999
		US 5863758 A	26-01-1999
US 5156844 A	20-10-1992	US 4892538 A	09-01-1990
		AT 86103 T	15-03-1993
		AU 2718488 A	14-06-1989
		AU 621326 B	12-03-1992
		CA 1335715 A	30-05-1995
		DE 3878918 A	08-04-1993
		DE 3878918 D	08-04-1993
		DE 3878918 T	17-06-1993
		DK 121690 A	13-07-1990
		EP 0388428 A	26-09-1990
		FI 95284 B	29-09-1995
		HK 1002406 A	21-08-1998
		JP 2780796 B	30-07-1998
		JP 3502534 T	13-06-1991
		KR 139223 B	15-05-1998
		NO 180031 B	28-10-1996
		US RE35653 E	04-11-1997
		WO 8904655 A	01-06-1989
		US 5389535 A	14-02-1995
		US 5786216 A	28-07-1998
		US 5643773 A	01-07-1997
		US 5773286 A	30-06-1998
		US 5554148 A	10-09-1996
		US 5487739 A	30-01-1996
		US 5573528 A	12-11-1996
		US 5158881 A	27-10-1992
		US 5106627 A	21-04-1992
		US 5283187 A	01-02-1994
		US 5182111 A	26-01-1993
		US 5284761 A	08-02-1994
		US 5871472 A	16-02-1999
		US 5418154 A	23-05-1995
		AT 89485 T	15-06-1993
		AU 632827 B	14-01-1993
		AU 5856590 A	08-01-1991
		CA 2062746 A, C	22-12-1990
		DE 69001672 D	24-06-1993
		DE 69001672 T	23-12-1993
		DK 478671 T	18-10-1993
		EP 0478671 A	08-04-1992

Form PCT/ISA/210 (patent family annex) (July 1992)

INTERNATIONAL SEARCH REPORT

Information on patent family members

1. International Application No

PCT/US 00/15102

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5156844 A		ES 2058923 T JP 2738881 B JP 5500620 T KR 141583 B NO 300488 B WO 9015637 A US 5474547 A	01-11-1994 08-04-1998 12-02-1993 15-06-1998 09-06-1997 27-12-1990 12-12-1995
US 5865796 A	02-02-1999	US 5584807 A AU 674815 B AU 1729595 A BR 9505691 A CA 2158733 A CN 1124460 A EP 0690732 A JP 8509131 T NZ 279995 A RU 2134295 C WO 9519799 A	17-12-1996 09-01-1997 08-08-1995 16-01-1996 27-07-1995 12-06-1996 10-01-1996 01-10-1996 27-04-1998 10-08-1999 27-07-1995
EP 0835894 A	15-04-1998	DE 19641334 A US 6031069 A	09-04-1998 29-02-2000

Form PCT/ISA/210 (patent family annex) (July 1992)